

CONNECTORS FOR TELEDUCTS

Technical specification

Endstop



| Size(mm.) | Art.Nr. | MOQ |
|-----------|-----------|-----|
| 16 | 35-16x16s | 75 |
| 20 | 35-20x20s | 90 |
| 25 | 35-25x25s | 60 |
| 32 | 35-32x32s | 36 |
| 40 | 35-40x40s | 36 |
| 50 | 35-50x50s | 18 |

Features :

- For use with HDPE pipes that comply with ISO 4427, EN 12201 and DIN 8074.
- Connects to metal and plastic accessories with ISO 7 threads.
- Made from top quality raw materials approved for drinking water by WRc, DVGW and KIWA.
- Allows easy and quick mounting without loss of parts.
- Unbreakable, corrosion-resistant and resistant to most chemicals.
- Stands up to tough working conditions, pipe bending and pulling.
- Complies with International Standards.

Materials :

- Grip Ring- Acetal
- Nut - PPB UV stabilized with carbon black
- D-Ring - Nitril -Butyl Rubber
- Body - PPB UV stabilized with carbon black

Performance :

- Maximum Working Temperature :

| | |
|---------------|-------|
| Polypropylene | 100°C |
| Acetal | 80°C |
- Working Conditions for 50 Year Lifetime :

| Working Temperature | Working Pressure |
|---------------------|------------------|
| up to 23°C | 16 bar |
| 40°C | 7 bar |
| 70°C | 4 bar |